



Revolutionising your family's boating experience.

This beautifully designed, in-built airstation is here to maximize quality time on the water.

At the push of a button, ATMOS is ready to inflate your paddleboards, towables and more: simply set the target pressure and let ATMOS do all the hard work.

Utilizing Scanstrut's outdoor technology DNA, this is waterproof on-board air that's engineered to thrive in the harsh marine environment.

Technical information

Max pressure output 20 PSI/1.37 BAR

Input voltage

system (10-14V)

12V Battery

Waterproof rating

IPX6 waterproof front and back

Max current

draw 12A (140W) Two stage pump

Stage 1 = 0 - 1 PSIStage 2 = 1.1 - 20 PSI

Standby current draw

0.02W Max

The design

The front

Take control with ease with the Soft Touch TPE buttons and cutting-edge LCD display. Specially crafted for the challenging marine environment, the buttons feature a non-slip texture that provides a tactile surface, even with wet hands and the bright, wide viewing angle display means you can have a great view from any place on the boat, even on the brightest days.



The back

Easily integrate ATMOS into your boat with its compact and shallow design. The versatile airstation can be installed in a variety of locations, including seating, consoles, or by the swim platform, making it convenient and accessible wherever it's needed. Easily installed into any panel using 10 self-tapping screws, with a foam gasket included to ensure a secure and waterproof fit.



The side

The minimum cavity depth required is 110mm (4.33") and it can be installed at an angle ranging from +10° to -30° from vertical. The power cable length is 500mm (20") with a wire gauge of 2.0mm2 (14 AWG). please note that there are no end-user serviceable parts.



Featuring next-gen air pump technology to provide fast, effortless inflation (and deflation) for your on-water toys. Compact and shallow, ATMOS fits into almost any panel on board such as seating, consoles, or near the swim platform. Now you have ready-to-go air, right where it's needed, for even more family fun on the water.



Towables Inflate: 3+ mins Deflate: 1 min



10ft SUP Inflate: 6-8 mins Deflate: 1 min



4M Platform Inflate: 15+ mins Deflate: 3+ min

Our Testing Ethos

The testing standard at Scanstrut is encapsulated by the acronym SCA, which stands for Safe, Certified, and Approved. With over 35 years of experience and expertise in designing products for outdoor use, we design our products to be able to thrive in the harshest of outdoor environments.



